

SECTION 09050 – INTERIOR/ EXTERIOR FINISHES, MATERIALS AND FINISH SCHEDULE

VAMC: West Texas VA HealthCare System-Big Springs
Location:300 Veterans Blvd, Big Spring, Texas 79720
Project no. and Name: VA 519-09-102 / Interior Finishes
Submission: Construction Documents
Date:5/12/08

**SECTION 09050
INTERIOR / EXTERIOR FINISHES, MATERIALS AND FINISH SCHEDULE**

PART I - GENERAL

1.1 DESCRIPTION

This section contains a coordinated system in which requirements for materials specified in other sections shown are identified by abbreviated material names and finish codes in the room finish schedule or shown for other locations.

1.2 MANUFACTURERS

Manufacturer's trade names and numbers used herein are only to identify colors, finishes, textures and patterns. Products of other manufacturer's equivalent to colors, finishes, textures and patterns of manufacturers listed that meet requirements of technical specifications will be acceptable upon approval in writing by contracting officer for finish requirements.

1.3 SUBMITALS

Submit in accordance with Section 01340, Samples and Shop Drawings provide quadruplicate samples for color approval of materials and finishes specified in this section.

1.4 APPLICABLE PUBLICATIONS

- A. Publications listed below form a part of this specification to the extent referenced. Publications are referenced in text by basic designation only.
- B. MASTER PAINTING INSTITUTE: (MPI)
2001.....Architectural Painting Specification Manual

PART 2- PRODUCTS

General Note: *Equal or superior quality products may be considered for the following specifications. Color, texture, profile and dimensional criteria must conform closely to the specified materials and must coordinate with all other work. Alternates or substitutions must be submitted for review and approval at time of bid submittals.*

06410 PLASTIC LAMINATE

- PL1 Formica (*general millwork*)
7265-58 Sandstone, Matte Finish
- PL2 Wilsonart (*Nurse Station laminate*)
D494-60 Antique Copper LS

6650 SPECIALTY SURFACE

- SS1 Wilsonart/Cambria
Style: Sutton
Color: 1760
Finish: polished
Gauge: $\frac{3}{4}$ "
Edge Profile: straight edge
- SS2 3-Form (used at Nurse Station as decorative banding, see elevation and as "Art" pieces)
(call product representative for additional information: Michele Berg 512 592-1800)
Style: Capiz Honey 2"/Sienna 2"
Front Finish: Sandstone
Back Finish: Sandstone
Sheet size options: 4' x 8', 4' x 10'
Gauge: $\frac{1}{4}$ "
Mounting Instructions: Installer must provide appropriate blocking and anchoring.
Smoke Density: ASTM D 2843-99, less than 75% (passes)
Flame Spread: ASTM D 635-98, CC1 rating, burn < 1" min. (passes)

Fire Rating: ASTM E84, Class B

Note: For "Art" application (see elevation on ID1.3 Drawing):

Order 1 sheet cut into 6 equal sections, 2' x2', Cutting & flame-polish edges by the manufacturer. Install on wall at designated locations with stainless steel stand-off mounts, 1" barrel style part #3-15-0725. Installer must provide appropriate blocking and anchoring.

09300 CERAMIC TILE

CT1 American Olean Tile (toilet room walls)
 Style: Porte Leona Porcelain Tile
 Size: 13" x 13" (also available as 2"x 2")
 Tile Thickness: 5/16"
 Grout Width Recommendation: 3/16"
 Grout: Use G1
Color: Avorio PL90
 (Bullnose Trim: S43E9 (3" x 13") if required)

09310 CERAMIC TILE GROUT

G1 Laticrete Spectra-Lock
 Color: 23 Antique White
 Grout Type: ANSI-A118.6-H2

09540 CEILING SUSPENSION TILES

ACT-1 Armstrong
 Minaboard Cortega , 2' X 2'(to match existing)
 Grid: match existing

9650 RESILIENT FLOOR TILE

VCT-1 Mannington Commercial
 Style: Solid Point
 Color: 337 Toasted Sesame
 Size: 12"x12"
 Gauge: 1/8"
 Fire Rating: ASTM E-84 Class 1

- VCT-2 Mannington Commercial
Style: Brushwork Brights
Color: 727 Deep Ochre
Size: 12"x12"
Gauge: 1/8"
Fire Rating: ASTM E-84 Class 1
- VCT-3 Mannington Commercial
Style: ColorPoint
Color: 659 Sable
Size: 12"x12"
Gauge: 1/8"
Fire Rating: ASTM E-84 Class 1
- VCT-4 Mannington Commercial
Style: SolidPoint
Color: 315 Sour Apple
- VCT-5 Mannington Commercial
Style: Brushwork
Color: 715 Baltic Green
- VCT-6 Mannington Commercial
Style: Solidpoint
Color: 338 Cherrywood
- VCT-7 Armstrong (Deduct alternate for RF-1)
Style: Safety Zone Slip Retardant Resilient Tile
Color: to be selected
Size: 12"x12"
Gauge: 1/8"
Fire Rating: ASTM E-84 Class 1
- VCT-8 Armstrong (Deduct alternate for RF-2)
Style: Safety Zone Slip Retardant Resilient Tile
Color: to be selected
- VCT-9 Armstrong (Deduct alternate for RF-3)
Style: Safety Zone Slip Retardant Resilient Tile
Color: to be selected

9650 RESILIENT FLOOR TILE (Continued.....)

VCT-10 Armstrong (Deduct alternate for RF-4)
Style: Safety Zone Slip Retardant Resilient Tile
Color: to be selected

VCT-11 Armstrong (Deduct alternate for RF-5)
Style: Safety Zone Slip Retardant Resilient Tile
Color: to be selected

VCT-12 Armstrong
Style: Safety Zone Slip Retardant Resilient Tile
Color: to be selected

9650 RESILIENT SHEET FLOORING

SV-1 Johnsonite
Style: Tarkett Safe-T Sheet Homogeneous Vinyl Flooring
Color: 125 Raw Hide
Size: 6'6" wide x 75'5" Linear Feet
Gauge: 0.080", Wear Layer Thickness: 0.80"
Weight: 5.3 lbs. sq. yd.
Static Load Limit: 125/800 lbs/sq. in.
Slip Resistance: >0.6 COF (ASTM D2047)
Water Resistance: Waterproof (SIS 923511)
Critical Radiant Flux: ASTM E 648 Class 1 Interior Floor Finish
Smoke Density: ASTM E 662- 450 or less
Adhesive: per manufacturer's requirements
Seaming: Heat weld
Welding Rod: 1289125

9650 RUBBER FLOORING

Except where specifically noted, heat-welding is not required for rubber floor.

- RF-1 Nora Rubber Flooring
 - Style: Environcare
 - Color: Russian Cypress 2786
 - Size: 15m x 1.22 m / 49.2' x 4'
 - Gauge: 0.08"
 - Static Load Limit: ASTM F-970: ≤ 0.005 " (1,000lbs./sq.inch)
 - Rolling Load Limit: 450 psi
 - Coefficient of Friction: ASTM D2047-82: ≥ 0.6 "
 - Critical Radiant Flux: ASTM E-648: Class 1
 - Smoke Density: 450 or less

- RF-2 Nora Rubber Flooring
 - Style: Environcare
 - Color: Sweet Olive 2968

- RF-3 Nora Rubber Flooring
 - Style: Environcare
 - Color: 2787 Driftwood

- RF-4 Nora Rubber Flooring
 - Style: Environcare
 - Color: 2949 Sage

- RF-5 Nora Rubber Flooring
 - Style: Environcare
 - Color: 2948 Veiled Dusk

- RF-6 Nora Rubber Flooring
 - Style: Environcare
 - Color: Pampas Grass 2969

09650 RUBBER COVE BASE and TRANSITION STRIPS

RB1 Johnsonite Rubber Cove Base
 Size: 4" , continuous roll
 Gauge: 1/8"
 Color: 45 Sandalwood

RB2 Johnsonite Millwork Base
 Profile: Silhouette MW-XX-J
 Size: 4"
 Gauge: 1/8"
 Color: 45 Sandalwood

T1 Johnsonite
 Transition Strip
 Color: 45 Sandalwood

09680 CARPET

C1 Mohawk (Hospital Standard)
 Style: Remix Modular BT138
 Color: 7978 Rock Party
 Size: 24" x 24" carpet tiles
 Installation direction: brick
 Fiber System: 100% Eco Solution Q Premium Branded Nylon
 Dye Method: Solution Dyed
 Construction: Multi-loop
 Gauge: 1/12"
 Stitches per inch: 10.66
 Tufted Yarn Weight: 26
 Finished Pile Thickness: 0.144"
 Primary Backing: Synthetic
 Secondary Backing: Ecoworx
 Flammability Rating: Passes Methanamine Pill Test (DOC FF #1-70)
 Flooring Radiant Panel: Exceeds minimum requirements of ASTM E-648
 Warranty: Lifetime Commercial Limited Warranty

09800 PAINT

Painting Subcontractor must provide 3'x3' paint samples on site for approval by Interior Designer.

- Standard Trim finish: Semi-gloss latex enamel Sherwin Williams Harmony Interior Latex Semi Gloss (B10 Series)
- Standard Wall finish: Satin latex Sherwin Williams Harmony Interior Latex Egg-Shell (B9 Series)
- Scrubable Wall finish: -S: Scrubable latex Sherwin Williams ProClassic Waterborne Interior Acrylic Semi-Gloss Enamel (B31 Series) or equal
- P1 Sherwin Williams
Color: SW6106 Kilim Beige
- P2 Sherwin Williams
Color: SW6108 Latte
- P3 Sherwin Williams
Color: SW6109 Hopsack (*trim and metal door frames*)
- P4 Sherwin Williams
Color: SW6115 Totally Tan (*accent color*)
- P6 Sherwin Williams
Color: SW6178 Clary Sage (*accent color*)
- P7 Sherwin Williams
Color: SW6214 Underseas (*accent color*)
- P8 Sherwin Williams
Color: Ceiling White
- ST1 Stain Color: to match existing doors

09955 WALLCOVERING

Note: Perforate all vinyl wallcoverings for use on "exterior facing" walls.

- WC-1 National (800 222-1028)
 Style: Zanobi
 Color: LXB-ZAN-02 Troi
 Weight: Type 11
 Width: 52"-54" wide
 Pattern Match: Reversible/Straight Across match
 Backing: 100% Polyester Osnaburg
 Packing: 30 lin.yd. bolts
 Microventing: 30 yd. minimum, \$1.20/yd, 2 week lead time
 Fire Rating: Class A/ASTM E-84
- WC-2 Tri-Kes (800) 200-8120
 Book: Source One
 Style: Caspian 2VJS-10 Tan
 Weight: Type 11, 21 oz
 Width: 54" wide
 Pattern Match: Random Match/ Reverse Hang
 Backing: Non Woven
 Packing: 30 lin.yd. bolts
 Fire Rating: Class A/ASTM E-84
- WC-3 National (800 222-1028)
 Style: Zanobi
 Color: color to be selected

10260 WALL PROTECTION**WALL & CORNER GUARDS, HANDRAILS, CRASHRAILS, & BUMPER RAILS**

- WP-1 Koroguard (800 628-0449)
 Color: Sienna
 Gauge: 0.080
 Texture: Pebblette
- HR-1 Koroguard (Handrail)
 Color: Sienna
 Gauge: 0.080
 Texture: Pebblette

12550 CUBICLE CURTAINS

CC-1 Maharam

Style: Semaphore 511442

Color: 004 Glow

Content: 50% Trivera CS Bioactive Polyester Polyester, 50% Polyester

Width: 72"

Repeat: 13-7/8"V, 72"H.

Fire Rating: Inherently flame resistant.

Cleaning Instructions: Washable up to 160 degrees

Mesh: EZE-Mesh in color: to be selected

or alternate: Carnegie

Style: Rain Forest #4158

Color: 2

Content: 100% Trivera CS Bioactive Polyester

Width: 72"

Repeat: "V, "H.

Fire Rating: Inherently flame resistant.

Cleaning Instructions: Washable up to 160 degrees

Mesh: EZE-Mesh in color: to be selected

3.3 ROOM FINISH SCHEDULE

- A. Match adjoining or existing similar surfaces colors, textures or patterns where disturbed or damaged by alterations or new work when not scheduled.
- B. **ROOM FINISH SCHEDULE: REFER TO FINISH SCHEDULE FROM OBRENTZ DESIGN (DATED 5/12/08) FOLLOWING THIS SECTION.**

--- E N D---